


AtmosAir 508FC



508FC pictured

SPECIFICATIONS

Air Flow Capacity.....up to 15,000 CFM*
 Pressure Drop.....minimum (see Fig. 1)
 Housing Material.....22-gauge powder-coated steel
 Weight.....22.5 pounds
 Maximum Operation Temperature.....200° F (60° C)

ELECTRICAL

Voltage.....115 or 240 VAC
 Frequency.....60/50 Hz
 Power Consumption.....50 watts
 Current Draw.....0.4-0.6 amps
 Internal Fuse.....1.5 amp
 Field Electrical Connection.....Junction Box

IONIZATION TUBE


Material.....Multi-core Composite, Stainless Steel
 Number.....Eight (8)
 Size.....F (21")
 Tube Life.....17,600 Hours*
 *dependent on conditions and annual tube maintenance.

DIMENSIONS.....see Figure 2

APPROVALS

Underwriters Laboratories Inc. listed as plenum-rated per UL 1995, 867; file # 313742. Energy Star Certified.

FIGURE 2



APPLICATION

The AtmosAir 508FC ionization system is intended to be mounted in the supply duct or air handler of a heating, cooling, or ventilating system. The unit is intended to operate only when air flow is present, thus, power to the ionization unit should be interlocked with fan operation, or controlled via an air pressure switch. The size and number of ionization systems is dependent upon the airflow, size of the space, and severity of the pollution and odors. Ionization can be adjusted with a 5-step knob.

OPTIONAL ACCESSORIES

Air Pressure Switch; Mounting Bracket; Timer; Remote Monitoring Panel; Remote Ion Switch; Remote indicator lights.

FIGURE 1

